

DN	PN	A	B	C	D	E	F	G	H	
		mm	mm	mm	mm	mm	mm	mm	mm	
500	2.5,6	645	508	24	68	15	538	12	7.1	
	10	670		28	75	16	540		7.1	
	16	715		34	90	16	546		8	
	25	730		44	125	20	558		10	
	40	755		52	140	20	562		14.2	
600	2.5,6	755	610	24	70	16	640	12	7.1	
	10	780		28	80	18	640		7.1	
	16	840		36	95	18	650		8.8	
	25	845		46	125	20	660		11	
	40	890		60	150	20	666		16	
700	2.5	860	711	24	70	16	740	12	.1	
	6	860		24	70		740		7.1	
	10	895		30	80	18	746		8	
	16	910		36	100	18	750		8.8	
	25	960		46	125	20	760		12.5	
800	2.5	975	813	26	70	16	842	12	.1	
	6	975		24	70		842		7.1	
	10	1015		32	90	18	848		8	
	16	1025		38	105	20	848		10	
	25	1085		50	135	22	864		14.2	
900	2.5	1075	914	26	70	16	942	12	.1	
	6	1075		26	70		942		7.1	
	10	1115		34	95	20	948		10	
	16	1125		40	110	20	948		10	
	25	1185		54	145	24	968		16	
1000	2.5	1175	1016	26	70	16	1045	12	.1	
	6	1175		26	70		1045		7.1	
	10	1230		34	95	20	1050		10	
	16	1255		42	120	22	1056		10	
	25	1320		58	155	24	1070		17.5	
1200	2.5	1375	1220	26	70	16	1245	16	.1	
	6	1405		28	90	20	1248	8		
	10	1455		38	115	25	1256	12	11	
	16	1485		48	130	30	1260	12.5		
	25	1575		66	170	35	1280	17.5		
1400	2.5	1575	1420	26	70	16	1445	16	.1	
	6	1630		32	90	20	1452	8		
	10	1675		42	120	25	1460	12	12	
	16	1685		52	145	30	1465	14.2		
	25	1790		66	170	35	1480	17.5		
1600	2.5	1790	1620	26	80	20	1645	16	.1	
	6	1830		34	90		1655		9	
	10	1915		46	130	25	1666		12	14
	16	1930		58	160	35	1668		16	
	25	1990		66	170	35	1670		17.5	
1800	2.5	1990	1820	26	80	20	1845	16	.1	
	6	2045		36	100		1855		10	
	10	2115		50	140	30	1866		15	15
	16	2130		62	170	35	1870		17.5	
	25	2190		66	170	35	1870		17.5	
2000	2.5	2190	2020	26	80	22	2045	16	.1	
	6	2265		38	110		25		2058	11
	10	2325		54	150	30	2070		15	16
	16	2345		66	190	40	2072		20	
	25	2415		76	220	45	2080		22.5	

Notes

- For drilling details see page 8-64.
- For tolerances see page 8-61.
- For facing types and dimensions see page 8-62.
- 1 To be specified by the purchaser.